

Product Specifications



P554004 LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

• Keep oil clean by capturing contaminants that cause engine damage.

• Include heavy duty components that are built to perform, built to last.

• Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	4.25 inch (108 mm)
Thread Size	1 1/8-16 UN
Length	10.31 inch (262 mm)
Gasket OD	3.90 inch (99 mm)
Gasket ID	3.54 inch (90 mm)
Efficiency 99%	40 micron
Efficiency Test Std	SAE J1858
Media Type	Cellulose
Collapse Burst	149 psi (10.3 bar)

Туре	Full-Flow
Style	Spin-On
Primary Application	CAT 2P4004 Not for EURO5/6 engines after 01/2019
Packaged Dimensions	
Packaged Length	0.35 FT
Packaged Width	0.35 FT
Packaged Height	0.89 FT
Packaged Weight	2.33 lb (1.058 kg)
Packaged Volume	0.11 ft3 (0.003 m3)
Other Information	
NMFC Code	069095-02

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.

742330044506

UPC Code